



Nordstrom X-195 Valve Sealant

X-195 VALVE SEALANT IS A FLUOROSILICONE-BASED PRODUCT THICKENED WITH MINERAL FILLERS DESIGNED FOR USE WHERE EXTREME CHEMICAL RESISTANCE IS REQUIRED. X-195 VALVE SEALANT PROVIDES EXCELLENT CHEMICAL RESISTANCE TO LIQUID AND GASEOUS ALIPHATIC HYDROCARBONS INCLUDING CRUDE OIL AND DISTILLATES, NATURAL GAS, GASOLINE, KEROSENE, AND FUEL OILS. IT CAN ALSO BE USED IN CONJUNCTION WITH STRONG ACIDS AND ALKALIES.

X-195 VALVE SEALANT IS FORMULATED SPECIFICALLY FOR USE IN LUBRICATED GATE VALVES AND IS NOT INTENDED FOR USE IN PLUG OR BALL VALVES.

Recommended Temperature Range

-20° to 400°F (-29° to 204°C)

Typical Physical Properties

Color		Beige	
Density (g/cm ³)		1.29	
Penetration @ 77° F (25°C),	Unworked	226	
	Worked	278	
Equivalent NLGI Grade		2	
Dropping Point °F		>500	
		°C	>260
Flash Point °F		565	
		°C	296

The information and data presented are based upon laboratory evaluation. However, because of the varied conditions under which this product may be used, the same results as those described here may not be obtained. Samples are available, and each user should independently determine the suitability of this product for their specific purposes.

Date: 9/8/2005